



## DATA SHEET 29 – FIG TC704 CONICAL (WITCHES HAT) STRAINER

**SIZES:** 1" to 36" NB Larger on request



**TO SUIT FLANGES TO:** ANSI B16.5/47 series A  
BS4504/DIN  
BS10  
JIS

**END CONNECTIONS:** RF / RTJ

**STANDARDS:** EN10204 2.1

**FINISH:** None as welded

**NDT:** PMI on request



Dimensions approx (mm)

NB	A1 150 RF	A1 300 RF	A1 600 RF	A2	B Short Pattern	B Long Pattern	~Weight KG Short Pattern	~Weight KG Long Pattern
1"/25mm	62	69	69	22	38	50	0.2	0.2
1½" 32mm	70	74	74	28	65	89	0.2	0.25
1½" 40mm	79	88	88	31	101	139	0.2	0.26
2" 50mm	98	104	104	44	114	152	0.2	0.28
2½" 65mm	116	122	122	64	120	189		0.32
3" 80mm	130	142	142	67	165	228	0.4	0.4
4" 100mm	168	174	187	88	215	292	0.6	0.7
5" 125mm	187	207	232	109	300	392	1.0	1.3
6" 150mm	215	244	260	139	330	431	1.1	1.5
8" 200mm	273	301	314	181	431	584	2.0	2.7
10" 250mm	333	355	393	228	533	685	2.7	3.4
12" 300mm	403	415	450	276	635	825	3.6	4.9
14" 350mm	444	479	485	320	660	889	4.5	5.4
16" 400mm	508	533	558	368	749	990	5.4	7.2
18" 450mm	542	590	606	415	838	1117	6.8	9.5
20" 500mm	600	647	676	466	939	1244	9.0	11.7
24" 600mm	711	768	784	568	1117	1473	12.2	16.3
28" 700mm	815	880	895	680	1305	1729	16.8	22.1
30" 800mm	911	906	936	967	1600	2130	25	40
36" 900mm	1040	1110	1120	840	1830	2435	30	45

**NOTES**

1. Standard screen – 3 mm perf. (Mesh overlay available on request)
2. Alternative length **B** available on request or to suit process conditions
3. Standard flow direction is from outside of cone to in.
4. Screen handle/Indent tab will be stamped to indicate size, rating & tag no where applicable
5. Rings are as rolled un-machined as standard. (Machined rings available on request)
6. **A1** dimensions for other flange rating available on request
7. Screens are not pressure retaining items and should not be exposed to a differential pressure in excess of 0.5 Bar G without our consent.
8. Manufactured in the UK - Materials from UK/EU stockists

**Materials of construction**

ITEM	STAINLESS STEEL	
1/2 CONE (FABRICATED) / MESH	304	316
3 RING/TAB	304	316

**NOTES**

1. Other materials such 316LSS, **Monel**, **Hastelloy**, **Inconel**, **Duplex** & **Super Duplex stainless steels** and other special alloys available on request
2. High pressure units available on request

All data is subject to confirmation at the time of order. Our policy is one of continual improvement and we reserve the right to amend details without prior notice. This datasheet, its concept, design and "copyright" are the property of Kaysafe Engineering Limited and cannot be legally copied or reproduced without the written authority of said Company.