



## DATA SHEET 2 – FIG 707 300 Y TYPE STRAINER

**SIZES:** 2" to 24" NB

**PRESSURE RATING:** ANSI CLASS 300


**END CONNECTIONS:** RF / RTJ / BW

**STANDARDS:** ANSI B16.10. ANSI B16.5.

**FINISH:** Manufactures' rust preventative standard paint on Carbon steel – As cast on Stainless steel (Special paint finish or lining available on request)

**NDT:** Hydro test as standard (X Ray / MPI/DPI/PMI available on request)

**CERTIFICATION** EN10204 3.1 (3.2 on request)  
NACE MR01-75  
PED 2014/68/EU (CE marked) (Formerly 97/23/EC)



Dimensions approx (mm)

NB	A	B	C (Screen removal)	KG RF	KG BW	NB	A	B	C (Screen removal)	KG RF	KG BW
2"	267	215	310	19	14	12"	711	699	1150	420	325
3"	318	270	390	34	23	14"	838	865	1420	670	526
4"	356	325	465	60	41	16"	914	910	1510	758	562
6"	445	440	670	113	79	18"	978	910	1510	863	615
8"	559	500	790	186	137	20"	1016	1060	1800	1125	885
10"	622	538	820	254	182	24"	1346	1300	2220	1625	1180

**NOTES**

1. Drain plug –  $\frac{3}{4}$ " NPT. Flanged or SW drain available on request
2. Standard screen – 1.5 mm perf. Mesh & Perf changes available on request
3. Screens are not pressure retaining items and should not be exposed to a differential pressure in excess of 0.5 Bar G without our consent.
4. Manufactured in the EU from EU & world wide source materials

### Materials of construction

<u>ITEM</u>		<u>CARBON STEEL</u>		<u>STAINLESS STEEL</u>
1	BODY (CAST)	ASTM A216 WCB	ASTM A352 LCC/LCB	ASTM A351 CF8M
2	SCREEN **	304/316 SS		316SS
3	COVER GASKET **	Spiral wound 316SS / Non asbestos		
4	COVER (CAST/FORGED)	ASTM A105N/ A216 WCB	ASTM A350 LF2/A352 LCC/LCB	ASTM A182 F316SS
5	BOLTING	B7 / 2H	L7 / Gr.4	B8 / Gr. 8
6	DRAIN PLUG	ASTM A105N	ASTM A350 LF2/A182 F316	ASTM A182 F316SS

**NOTES**

1. Other materials including CF8, CF3, LCB, LCC, CHROME-MOLY CS, MONEL, DUPLEX & SUPER DUPLEX and other special alloys available on request
2. Special gaskets / bolting available on request
3. SPARES AS MARKED \*\*